



Universal Tool
Air Tools for Industry



UT2964 ADJUSTABLE CLUTCH SCREWDRIVER



FEATURES & SPECIFICATIONS

- Excellent for self-tapping
- Thumb operated forward/reverse
- Through handle exhaust
- Best for: Light production using self-tapping fasteners

| Model # | Motor (hp) | Motor (Kw) | Torque Range (in. lbs) | Speed (rpm) | Exhaust | Chuck | Weight (lbs) | Weight (Kg) | Length (in) | Length (mm) | Air Inlet (npt) | Rec. Hose (id. in) | Air Cons. (cfm) | Avg. Air Cons. (cfm) |
|---------|------------|------------|------------------------|-------------|---------|---------------|--------------|-------------|-------------|-------------|-----------------|--------------------|-----------------|----------------------|
| UT2964 | 0.05 | 0.37 | 25-125 | 1,800 | Handle | 1/4" Hex Q.C. | 2.50 | 1.10 | 8.50 | 190 | 1/4" | 3/8" | 16.00 | 4.00 |

Recommended Air Pressure of 90 psi - 6.2 bar

Universal Tool, a Brand of Continental Tool Group, Inc. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403
www.UniversalToolUSA • (800) 356-3392

