



**Universal Tool**  
Air Tools for Industry



# UT8065R 3/8" HIGH PERFORMANCE INDUSTRIAL IMPACT WRENCH



## FEATURES & SPECIFICATIONS

- Refined design twin hammer and biased motors provide high torque
- Low weight composite housings
- Ergonomic trigger design with feather control
- Push button forward/reverse for instant change in direction
- Four position power management switch conveniently located in back cap
- Titanium finish hammer case
- Built-in side impact buffers
- Over-molded ergonomic grips
- Ring Retainer

Model	Working Trq (ft.-lb.)	Working Trq (nm)	Max Trq (ft.-lb.)	Max Trq (nm)	Speed (rpm)	Anvil	Socket Retainer	Exhaust	Weight (lb.)	Weight (kg)	Length (in.)	Length (mm)	Air Inlet (npt)	Hose (I.D. in.)	Air Cons (cfm)	Average (cfm)
UT8065R	50-450	68-610	500	675	11,000	3/8" Square	Friction Ring	Handle	3.00	1.40	6.10	155	1/4"	3/8	24	6.00

Recommended Air Pressure of 90 psi - 6.2 bar

Universal Tool, a Brand of Continental Tool Group, Inc. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403  
www.UniversalToolUSA • (800) 356-3392

