



Universal Tool
Air Tools for Industry



UT8475C 1" IMPACT WRENCH



FEATURES & SPECIFICATIONS

- Hard Hitting Twin Hammer Design
- 2,100 ft/lbs Maximum Torque
- Recessed Combined Power Management / Direction Mechanism
- Steel hammer case increases reliability
- Low-weight Impact Resistant Housing
- Combined Friction Ring/Through Hole Retaining System
- Best For: Heavy Plant & Vehicle Main

Model	Working Trq (ft-lb.)	Working Trq (nm)	Max Trq (ft-lb.)	Max Trq (nm)	Speed (rpm)	Anvil	Socket Retainer	Exhaust	Weight (lb.)	Weight (kg)	Length (in.)	Length (mm)	Air Inlet (npt)	Hose (I.D. in.)	Air Cons (cfm)	Average (cfm)
UT8475C	500-1650	678-2237	2,100	2,848	7,500	1" Square	Friction Ring / Combo	Bottom	12.96	5.90	10.7	273	3/8"	1/2	7.5	10.00

Recommended Air Pressure of 90 psi - 6.2 bar

Universal Tool, a Brand of Continental Tool Group, Inc. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403
www.UniversalToolUSA • (800) 356-3392

