



**Universal Tool**  
Air Tools for Industry



# UT8641C 1" IMPACT WRENCH



## FEATURES & SPECIFICATIONS

- 2800 ft-lb maximum torque
- The high energy two jaw clutch provides unmatched torque output and increases the life of the hammers beyond other impact mechanisms
- The two jaw clutch does not waste energy reducing air consumption
- The heavy duty built-in suspension/safety bail allows safe suspension of the tool when used overhead or at high levels
- UT8641C has through hole retainer and includes (3pc) retaining pin & ring
- The machined steel hammer case & rugged construction ensures reliability in the toughest conditions.
- The unique trigger with a rubber inlay increases operating comfort

Model	Working Trq (ft.-lb.)	Working Trq (nm)	Max Trq (ft.-lb.)	Max Trq (nm)	Speed (rpm)	Anvil	Socket Retainer	Exhaust	Weight (lb.)	Weight (kg)	Length (in.)	Length (mm)	Air Inlet (opt)	Hose (I.D. in.)	Air Cons (cfm)	Average (cfm)
UT8641C	500-1650	678-2237	2,800	3,796	4,300	1" Square	Through Hole	Top	23.30	10.60	14.30	363	1/2"	3/4	25.2	6.30

Recommended Air Pressure of 90 psi - 6.2 bar

Universal Tool, a Brand of Continental Tool Group, Inc. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403  
www.UniversalToolUSA • (800) 356-3392

