



**Universal Tool**  
Air Tools for Industry



# UT8895R REVERSIBLE 3/8" DRILL



## FEATURES & SPECIFICATIONS

- 0.9 HP Motor for ultimate stall resistance
- Fully caged gears with needle bearings for ultimate reliability
- Ported throttle valve for ultimate control and reliability
- Through handle exhaust with built-in silencing system
- Advanced ergonomically designed handle with "Softouch" coating offers ultimate comfort and reduced vibration
- Jacobs® industrial chuck for accuracy and durability
- Reversible models are ideal for reaming and rivet removal
- Best for: Continuous drilling in high volume applications

Model #	Motor (hp)	Motor (Kw)	Speed (rpm)	Exhaust	Chuck (in.)	Weight (lb)	Weight (kg)	Length (in)	Length (mm)	Air Inlet (npt)	Rec. Hose (id. in)	Air Cons. (cfm)	Avg. Air Cons. (cfm)
UT8895R	0.80	0.59	1,800	Handle	1/2	2.10	1.00	7.75	197	1/4"	3/8"	18.40	4.60

Recommended Air Pressure of 90 psi - 6.2 bar

Universal Tool, a Brand of Continental Tool Group, Inc. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403  
www.UniversalToolUSA • (800) 356-3392

