



**Universal Tool**  
Air Tools for Industry



# UT8966 POSITIVE CLUTCH SCREWDRIVER



## FEATURES & SPECIFICATIONS

- 0.9 HP Motor with direct drive with positive clutch
- Above trigger mounted reverse for rapid change in direction
- Precision engineered, for ultimate reliability
- Through handle exhaust with built-in silencing system
- Advanced ergonomically designed handle with “Softouch” coating offers ultimate comfort and reduced vibration
- Best for: High volume, high prevailing torque self-tapping

Model #	Motor (hp)	Motor (Kw)	Torque Range (in. lbs)	Speed (rpm)	Exhaust	Chuck	Weight (lbs)	Weight (Kg)	Length (in)	Length (mm)	Air Inlet (npt)	Rec. Hose (id. in)	Air Cons. (cfm)	Avg. Air Cons. (cfm)
UT8966	0.90	0.66	30-125	2,000	Handle	1/4" Hex Q.C.	2.50	1.10	6.80	172	1/4"	3/8	22.00	5.50

Recommended Air Pressure of 90 psi - 6.2 bar

Universal Tool, a Brand of Continental Tool Group, Inc. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403  
www.UniversalToolUSA • (800) 356-3392

