



Universal Tool
Air Tools for Industry



UT7560C-1 **1" Impact Wrench**



FEATURES & SPECIFICATIONS

- High energy two jaw clutch – 1,025 ft-lbs (1,388 N.m) maximum torque
- Pressure feed hammer lubrication for added reliability
- Three piece housing design eases maintenance
- Extra heavy duty steel hammer case for ultimate durability
- Built-in exhaust silencer system for noise control
- Best for: heavy plant and vehicle service

Model #	Working Torque ft-lbs (N.m)	Max. Torque ft-lbs (N.m)	Speed (RPM)	Exhaust	Anvil (in)	Weight lbs (kg)	Length in (mm)	Air Inlet NPT in (mm)	Hose I.D. in (mm)	Air Cons. (cfm)	Avg. Air Cons. (cfm)
UT7560C-1	232-800 (315-1,086)	1,025 (1,388)	5,700	Front	1 / Square	11.60 (5.30)	7.60 (193)	3/8 (9.53)	1/2 (12.70)	38	9.0

Recommended Air Pressure of 90 psi - 6.2 bar

Universal Tool, a Brand of Continental Tool Group, Inc. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403
www.UniversalToolUSA • (800) 356-3392

