



Universal Tool
Air Tools for Industry



UT8922 1/4" AIR-HYDRAULIC RIVETER



FEATURES & SPECIFICATIONS

- 3,500 Lb pull force allows use for rivets up to 1/4" including stainless
- Vac feature hold rivet for perpendicular applications
- Comfortable trigger with high-low setting
- Swivel air inlet for maneuverability
- Rubberized grip for comfort
- Detachable mandrel collector
- Built-in silencer reduces noise level
- Designed for continuous operation
- Supplied with four (4) nose pieces (3/32"-1/4") and an extra set of jaws

Model #	Nose Piece (in)	Traction Force (lb)	Rivet Capacity	Weight lbs (kg)	Length in. (mm)	Air Inlet (NPT)	Rec. Hose (id. in)	Air Cons. (cfm)	Avg. Air Cons (cfm)
UT8922	3/32", 1/8", 3/16", 1/4"	3,500	Up to 1/4" Stainless	4 (1.8)	13.25 (336)	1/4"	3/8"	1.5	0.4

Recommended Air Pressure of 90 psi - 6.2 bar

Universal Tool, a Brand of Continental Tool Group, Inc. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403
www.UniversalToolUSA • (800) 356-3392

