



Universal Tool

Air Tools for Industry



UT8897RS Aircraft Rivet Shaver



FEATURES & SPECIFICATIONS

- Precision Cutter adjustment of 0.0005"
- Ported valve for variable speed control
- Softouch coating for operator comfort
- Muffled through handle exhaust
- Reverse threaded skirt to keep vibration from affecting the shaving depth repeatability
- Best for: Aircraft rivets

Model #	Motor hp (kW)	Gear Ratio	Throttle Style	Speed (rpm)	Skirt in (mm)	Weight lbs (kg)	Length in (mm)	Air Cons. (cfm)	Avg. Air Cons. (cfm)
UT8897RS-1/4 ¹	0.90 (0.66)	1:1	Ported	20,000	1/4 (6.35)	2.60 (1.10)	7.75 (197)	22.00	4.60
UT8897RS-5/16 ¹	0.90 (0.66)	1:1	Ported	20,000	5/16 (7.94)	2.60 (1.10)	7.75 (197)	22.00	4.60
UT8897RS-3/8 ¹	0.90 (0.66)	1:1	Ported	20,000	3/8 (10.00)	2.60 (1.10)	7.75 (197)	22.00	4.60
UT8897RS-7/16 ¹	0.90 (0.66)	1:1	Ported	20,000	7/16 (11.11)	2.60 (1.10)	7.75 (197)	22.00	4.60
UT8897RS-1/2 ¹	0.90 (0.66)	1:1	Ported	20,000	1/2 (12.70)	2.60 (1.10)	7.75 (197)	22.00	4.60
UT8897RS-9/16 ¹	0.90(0.66)	1:1	Ported	20,000	9/16 (14.29)	2.60 (1.10)	7.75 (197)	22.00	4.60
UT8897RS-5/8 ¹	0.90 (0.66)	1:1	Ported	20,000	5/8 (15.88)	2.60 (1.10)	7.75 (197)	22.00	4.60

1. Handle Exhaust

Recommended Air Pressure: 90 PSI (6.2 Bar) | Air Inlet: 1/4" (6.35mm) NPT | Recommended Hose Size: 3/8" (10mm) I.D.

Universal Tool, a Brand of Continental Tool Group, Inc. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403
www.UniversalToolUSA • (800) 356-3392

