



Universal Tool
Air Tools for Industry



UT8963AT-17 AIR ON TOP AUTO SHUT-OFF SCREWDRIVER



FEATURES & SPECIFICATIONS

- Air on top feature allows for clean vertical suspension without trailing hoses
- Adjustable auto shut-off clutch for precision, smooth disengagement and minimum vibration
- A choice of speeds to fit your job, with convenient thumb operated reverse
- Precision engineered, for ultimate reliability
- Through handle exhaust with built-in silencing system and built-in suspension bail
- "Softouch" handle grip offers ultimate comfort and reduced vibration
- Trigger start
- Best for: Precision high volume assembly

Model #	Motor (hp)	Motor (Kw)	Torque Range (in. lbs)	Speed (rpm)	Exhaust	Chuck	Weight (lbs)	Weight (Kg)	Length (in)	Length (mm)	Air Inlet (npt)	Rec. Hose (id. in)	Air Cons. (cfm)	Avg. Air Cons. (cfm)
UT8963AT-17	0.50	0.37	5-30	1,700	Handle	1/4" Hex Q.C.	1.90	0.90	8.25	210	1/4"	3/8"	16.00	4.00

Recommended Air Pressure of 90 psi - 6.2 bar

Universal Tool, a Brand of Continental Tool Group, Inc. • 1660 Silver Beach Road, Suite 100, Lake Park, FL 33403
www.UniversalToolUSA • (800) 356-3392

